

## MULTIMAX MP 513 - Especificaciones técnicas



### Description

MULTIMAX MP 513 ha sido proyectado por BKT para utilizarlo con vehículos polivalentes en el sector de la municipalidad/mantenimiento y de transporte para uso agrícola y industrial. El neumático es perfecto para vehículos universales y camiones de fertilizante. Gracias a su robusta carcasa de nylon reforzada con cinturones de acero, MULTIMAX MP 513 permite transportar cargas pesadas a altas velocidades proporcionando una experiencia de conducción confortable. Asegura una vida operativa más larga así como optimas propiedades de auto-limpieza.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Vehículo universal • Camión de fertilizantes  
Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	425/75 R 20 MPT
LI/SS	148 G

## Dimensions International Standard

Section Width (mm)	421
Overall Diameter (mm)	1146
Static Loaded Radius (mm)	521
Rolling Circumference (mm)	3479
Rim Rec	13
Rim Alt	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
ECE	E11-54R-0016141

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0
90	1540	1810	2150	2490	2820	3150
65	1675	1965	2335	2705	3060	3420
40	1775	2085	2475	2865	3245	3625

Printed on 25/04/2024 19:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..