

MULTIMAX MP 513 - Especificaciones técnicas



Description

MULTIMAX MP 513 ha sido proyectado por BKT para utilizarlo con vehículos polivalentes en el sector de la municipalidad/mantenimiento y de transporte para uso agrícola y industrial. El neumático es perfecto para vehículos universales y camiones de fertilizante. Gracias a su robusta carcasa de nylon reforzada con cinturones de acero, MULTIMAX MP 513 permite transportar cargas pesadas a altas velocidades proporcionando una experiencia de conducción confortable. Asegura una vida operativa más larga así como optimas propiedades de auto-limpieza.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Vehículo universal • Camión de fertilizantes
Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	495/70 R 24 MPT
LI/SS	155 G

Dimensions International Standard

Section Width (mm)	499
Overall Diameter (mm)	1304
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3974
Rim Rec	W 16 L
Rim Alt	DW 15 L ; DW 16 L ; W 15 L
ECE	E4-54R-0029057

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1980	2340	2840	3250	3875
65	2150	2540	3085	3530	4205
40	2280	2695	3270	3740	4460

Printed on 25/04/2024 15:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..