

MULTIMAX MP 519 - Especificaciones técnicas



Description

MULTIMAX MP 519 es un neumático idóneo para camiones ligeros en todas las aplicaciones de transporte. La carcasa reforzada con cinturones de acero garantiza una excelente estabilidad a grandes velocidades (90 km/h). Gracias a la baja resistencia al rodamiento, el neumático asegura un consumo reducido de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Camión ligero

| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 7.50 R 16 LT |
| LI/SS | 109/107 G |

Dimensions International Standard

| | |
|-----------------------------------|--------------------|
| Ply Rating | 6 |
| Section Width (mm) | 220 |
| Overall Diameter (mm) | 810 |
| Static Loaded Radius (mm) | 377 |
| Rolling Circumference (mm) | 2449 |
| Rim Rec | 6.00 |
| Rim Alt | 5.50 F ; 6 L ; 7 L |

Load capacity (Kg)

| | km/h / bar | 3.5 |
|--|------------|------|
| | 90 LS | 1030 |
| | 90 LD | 975 |

Printed on 07/05/2024 2:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..