

MULTIMAX MP 519 - Ficha técnica



Description

MULTIMAX MP 519 es un neumático idóneo para camiones ligeros en todas las aplicaciones de transporte. La carcasa reforzada con cinturones de acero garantiza una excelente estabilidad a grandes velocidades (90 km/h). Gracias a la baja resistencia al rodamiento, el neumático asegura un consumo reducido de carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Camión ligero

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 R 16 LT	STANDARD	94053384	109/107 G	6	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	
7.50 R 16 LT	STANDARD	94063437	112/110G	8	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	E11-54R-0019046

Printed on 06/05/2024 21:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..