

MULTIMAX MP 525 - Especificaciones técnicas



Description

MULTIMAX MP 525 es un neumático radial polivalente All Steel diseñado para elevadores telescópicos, cargadoras compactas y motoniveladoras en aplicaciones agroindustriales. El neumático se ha desarrollado específicamente para transportar cargas pesadas a velocidades más altas por carretera y fuera de carretera. De hecho, el dibujo ancho y no-direccional de la banda de rodadura proporciona una tracción excepcional en cualquier superficie, además de excelentes propiedades de autolimpieza. El robusto flanco garantiza una estabilidad lateral excepcional en modalidad de levantamiento, lo que hace que la elección ideal para operaciones agrícolas y de manipulación de materiales. MULTIMAX MP 525 está realizado con una mezcla especial de la banda de rodadura resistente a los cortes y los desgarros, que garantiza una mayor vida útil del neumático gracias a su extraordinaria resistencia a todo tipo de cortes y pinchazos.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Cargadora compacta • Motoniveladora •
Elevador telescópico

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 (16.0/70 R 20)
LI/SS	152 J/168 A2

Dimensions International Standard

Overall Width (mm)	405
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	482
Rolling Circumference (mm)	3260
Rim Rec	13
Rim Alt	12; 13 SDC
ECE	E11-54R-0020576

Load capacity (Kg)

km/h / bar	6.00
100	3550
10	5600

Printed on 04/05/2024 7:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..