

MULTIMAX MP 538 - Ficha técnica



Description

MULTIMAX MP 538 es un neumático radial polivalente diseñado específicamente para diversas aplicaciones y maquinarias: las niveladoras y las cargadoras que operan en condiciones invernales, así como los elevadores telescópicos, los vehículos universales y las barredoras en el mantenimiento de carreteras.

Gracias a la robusta carcasa con cinturones de acero, el MULTIMAX MP 538 permite transportar cargas pesadas incluso a altas velocidades. Además, su exclusivo diseño de la banda de rodadura contribuye a mantener una excelente tracción sobre hielo y nieve.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Elevador telescópico • Vehículo universal
Industrial: Motoniveladora • Pala cargadora

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
405/70 R 20 MPT	STEEL BELTED	152 G	W13		407	1076	484	3289	TL

Printed on 28/04/2024 2:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..