

## MULTIMAX MT 518 - Especificaciones técnicas



### Description

MULTIMAX MT 518 ha sido específicamente desarrollado para camiones militares. Es un neumático con un dibujo de bloques en la banda de rodadura y cinturones de acero, caracterizado por una elevada resistencia a la perforación, así como una extraordinaria estabilidad. Además, MULTIMAX MT 518 permite que este neumático alcance altas velocidades y asegura un ciclo de vida prolongado.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Camión militar

Version	STANDARD
Type	TL
Tyre Size	36 X 12.5 R 16.5
LI/SS	129 N

## Dimensions International Standard

Section Width (mm)	315
Overall Diameter (mm)	902
Static Loaded Radius (mm)	420
Rolling Circumference (mm)	2758
Rim Rec	9.75
ECE	E11-54R-0017917

## Load capacity (Kg)

km/h / bar	4.5
140	1850

Printed on 25/04/2024 10:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..