

## PAC MASTER PLUS - Especificaciones técnicas



### Description

PAC MASTER PLUS es un neumático diagonal que se utiliza en las máquinas compactadoras. Se caracteriza por un área de contacto más ancha que ofrece una mayor estabilidad. Está realizado con una mezcla especial que proporciona una elevada resistencia al calor. PAC MASTER PLUS asegura un ciclo de vida prolongado del neumático.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Compactador

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

## Dimensions US Standard

Usa code	94048809
Ply Rating	14
Section Width (inch)	8.9
Overall Diameter (inch)	31.1
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	93.9
Rim Rec	6.0
Rim Alt	6.5
ECE	E11-106R-005322

## Load capacity (lbs)

mph / psi	127
5	6400
10	5070

Printed on 08/05/2024 21:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..