

PAC MASTER PLUS - Especificaciones técnicas



Description

PAC MASTER PLUS es un neumático diagonal que se utiliza en las máquinas compactadoras. Se caracteriza por un área de contacto más ancha que ofrece una mayor estabilidad. Está realizado con una mezcla especial que proporciona una elevada resistencia al calor. PAC MASTER PLUS asegura un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Compactador

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	14
Section Width (mm)	270
Overall Diameter (mm)	1005
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005359

Load capacity (Kg)

km/h / bar	7.25
10	4375
15	3445

Printed on 08/05/2024 20:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..