

PL 801 - Especificaciones técnicas



Description

PL 801 ha sido particularmente desarrollado para los rastrillos hileradores rotativos y los volteadores de heno, así como para las operaciones de logística realizadas con carretillas elevadoras. Este neumático ofrece una excelente estabilidad, así como una elevada resistencia a cualquier tipo de corte. PL 801 asegura un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora • Rastrillo hilerador rotativo •
Carretilla elevadora
Industrial: Carretilla elevadora

| | |
|-----------|---------------------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 250 - 15 (250/70 - 15) |

Dimensions International Standard

| | |
|-----------------------|-----------|
| Ply Rating | 20 |
| Section Width (mm) | 235 |
| Overall Diameter (mm) | 745 |
| Rim Rec | 7.50 BD |
| Rim Alt | 7.0 ; 7.5 |

Load capacity (Kg)

| km/h / bar | 10.00 |
|--------------------|-------|
| 25 LOAD WHEEL | 5040 |
| 25 STEER WHEEL | 3875 |
| 10 OTHER VEHICLES | 5040 |
| 25 OTHER VEHICLES | 3875 |
| STATIC SIDE LOADER | 5850 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 1:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..