

## PORT KING CLASSIC - Especificaciones técnicas



### Description

PORT KING CLASSIC es el neumático para puertos BKT de última generación, especialmente estudiado para maquinaria utilizada en la manipulación de contenedores. El neumático asegura la máxima eficiencia operativa y una estabilidad excepcional en la modalidad de levantamiento. Gracias a su robusta carcasa de nylon, PORT KING CLASSIC se caracteriza por su mayor capacidad de carga, minimizando el riesgo de rotura por impacto, desgarro y perforación. La nueva mezcla resistente al desgaste se ha desarrollado para asegurar un ciclo de vida prolongado del producto además del mejor rendimiento de la inversión.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Grúa Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

## Dimensions US Standard

Usa code	94054480
Ply Rating	40
Overall Width (inch)	20.8
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	195.1
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

## Load capacity (lbs)

mph / psi	145
5	50625

Printed on 04/06/2024 8:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..