

PORT KING PLUS - Especificaciones técnicas



Description

PORT KING PLUS ha sido específicamente proyectado para las grúas cargadoras de contenedores (Reach Stacker) que se utilizan en las operaciones de logística/transportes intermodales. Su profunda banda de rodadura se caracteriza por unos robustos tacos y está realizada con una mezcla especial que asegura un ciclo de vida prolongado del neumático. También hay disponible una versión con una mezcla particularmente resistente a las grietas en las ranuras de la banda de rodadura "GCRC" (groove crack resistant compound).

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Grúa Reach Stacker

Version	GCRC
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	40
Overall Width (mm)	528
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	4955
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	22950

Printed on 21/04/2024 22:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..