

PORTMAX PM 90 - Especificaciones técnicas



Description

PORTMAX PM 90 ha sido particularmente proyectado para las grúas cargadoras de contenedores en varias aplicaciones, como la manipulación industrial y acerías. La especial mezcla antiestática de la banda de rodadura asegura una buena resistencia al calor y un ciclo de vida prolongado del neumático. PORTMAX PM 90 ofrece una reducida resistencia al rodamiento, permitiendo un ahorro de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Grúa Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 33
LI/SS	214 A5

Dimensions International Standard

Overall Width (mm)	485
Overall Diameter (mm)	1845
Static Loaded Radius (mm)	857
Rolling Circumference (mm)	5624
Rim Rec	13.00/2.50
Rim Alt	13.00/2.50 IF
Star Rating	***

Load capacity (Kg)

km/h / bar	10.00
25	21200

Printed on 20/04/2024 17:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..