

## PORTMAX PM 93 PLUS - Especificaciones técnicas



### Description

PORTMAX PM 93 PLUS ha sido particularmente proyectado para las carretillas p rtico que se utilizan en las operaciones portuarias de manipulaci n de los contenedores. Este neum tico radial All Steel con cinturones de acero multiestrato garantiza una estabilidad y una durabilidad mejores. La especial mezcla antiest tica de la banda de rodadura asegura una vida m s larga del neum tico. PORTMAX PM 93 PLUS ofrece una reducida resistencia al rodamiento, permitiendo un ahorro de carburante.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Carretilla p rtico

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 R 25
LI/SS	200 A5

## Dimensions International Standard

Overall Width (mm)	425
Overall Diameter (mm)	1515
Static Loaded Radius (mm)	699
Rolling Circumference (mm)	4582
Rim Rec	11.25/2.0
Star Rating	**

## Load capacity (Kg)

km/h / bar	10
25	14000

Printed on 21/04/2024 23:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..