

PORTMAX PM 93 PLUS - Especificaciones técnicas



Description

PORTMAX PM 93 PLUS ha sido particularmente proyectado para las carretillas pórtico que se utilizan en las operaciones portuarias de manipulación de los contenedores. Este neumático radial All Steel con cinturones de acero multiestrato garantiza una estabilidad y una durabilidad mejores. La especial mezcla antiestática de la banda de rodadura asegura una vida más larga del neumático. PORTMAX PM 93 PLUS ofrece una reducida resistencia al rodamiento, permitiendo un ahorro de carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Carretilla pórtico

| | |
|-----------|------------|
| Version | INDUSTRIAL |
| Type | TL |
| Tyre Size | 16.00 R 25 |
| LI/SS | 200 A5 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94047680 |
| Overall Width (inch) | 16.7 |
| Overall Diameter (inch) | 59.6 |
| Static Loaded Radius (inch) | 27.5 |
| Rolling Circumference (inch) | 180.4 |
| Rim Rec | 11.25/2.0 |
| Star Rating | ** |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 145 |
| 15 | 30900 |

Printed on 21/04/2024 22:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..