

## PORTMAX PT 93 - Especificaciones técnicas



### Description

PORTMAX PT 93 es el neumático para tractores de terminal y remolques, concretamente fabricado para operaciones de servicio pesadas en las terminales portuarias y en los centros de logística. La banda de rodadura, proyectada con una mezcla especial antiestática, ofrece una particular resistencia al desgaste y al calor incluso en las situaciones más exigentes. PORTMAX PT 93 es el neumático ideal para todas las operaciones que requieran un alto grado de maniobrabilidad, además asegura un grip excelente y una avanzada durabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Tractor de terminal • Remolque

Version	INDUSTRIAL
Type	TL
Tyre Size	310/80 R 22.5
LI/SS	175 A8

## Dimensions US Standard

Usa code	94057764
Overall Width (inch)	12.1
Overall Diameter (inch)	42.1
Rim Rec	9.00

## Load capacity (lbs)

mph / psi	145
25	15200

Printed on 19/04/2024 23:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..