

PORTMAX PT 93 - Especificaciones técnicas



Description

PORTMAX PT 93 es el neumático para tractores de terminal y remolques, concretamente fabricado para operaciones de servicio pesadas en las terminales portuarias y en los centros de logística. La banda de rodadura, proyectada con una mezcla especial antiestática, ofrece una particular resistencia al desgaste y al calor incluso en las situaciones más exigentes. PORTMAX PT 93 es el neumático ideal para todas las operaciones que requieran un alto grado de maniobrabilidad, además asegura un grip excelente y una avanzada durabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Tractor de terminal • Remolque

Version	INDUSTRIAL
Type	TL
Tyre Size	315/60 R 22.5
LI/SS	170 A8

Dimensions International Standard

Overall Width (mm)	307
Overall Diameter (mm)	965
Rim Rec	9.75
Rim Alt	9.00

Load capacity (Kg)

km/h / bar	10.00
40	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 18:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..