

## POWER TRAX HD (SS) - Especificaciones técnicas



### Description

El POWER TRAX SS es un neumático de telas cruzadas especialmente diseñado para aplicaciones portuarias y de minería subterránea. Su profunda banda de rodadura y el flanco con un espesor extra, así como su robusta carcasa, se traducen en una extraordinaria durabilidad, minimizando el riesgo de perforación y de daños accidentales. Este neumático se caracteriza por una excelente resistencia a los cortes y las laceraciones, lo que hace que sea especialmente adecuado para superficies rugosas y duras. El borde de protección de la llanta, especialmente diseñado, protege el neumático en el área de la pestaña de la llanta contra desinflamientos y daños.

### UM

US Standard

### Construction

✚ BIAS

### Machinery

Industrial: Minicargadora compacta

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TL        |
| Tyre Size | 10 - 16.5 |

## Dimensions US Standard

|                              |          |
|------------------------------|----------|
| Usa code                     | 94017300 |
| Ply Rating                   | 10       |
| Section Width (inch)         | 10.6     |
| Overall Diameter (inch)      | 31.1     |
| Static Loaded Radius (inch)  | 14.2     |
| Rolling Circumference (inch) | 91.8     |
| Rim Rec                      | 8.25     |

ECE

## Load capacity (lbs)

| mph / psi | 75   |
|-----------|------|
| 5         | 4710 |
| 10        | 3710 |
| 15        | 3440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/05/2025 10:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..