

POWER TRAX - Especificaciones técnicas



Description

POWER TRAX es un neumático de primera calidad especialmente diseñado para el servicio pesado en remolques portuarios, manipuladores de contenedores vacíos o ECH y maquinarias de minería subterránea. Su profunda banda de rodadura y su resistente carcasa proporcionan una durabilidad excepcional, por lo que disminuye el riesgo de pinchazos y daños accidentales. POWER TRAX es el neumático ideal para operaciones duras y resistentes, gracias al exclusivo compuesto de la banda de rodadura, que proporciona una excelente resistencia a cortes y desperfectos.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Manipulador de contenedores vacíos
OTR: Vehículos para minería subterránea

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20
LI/SS	176 A5

Dimensions International Standard

Ply Rating	20
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.5
Rim Alt	9.0

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	9230
25 STEER WHEEL	7100
10 OTHER VEHICLES	9230
25 OTHER VEHICLES	7100
STATIC SIDE LOADER	10720

Printed on 26/04/2024 18:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..