

## POWERTRAILER SR 331 - Especificaciones técnicas



### Description

POWERTRAILER SR 331 es el nuevo neumático radial All Steel de BKT diseñado específicamente para remolques y camiones cisterna en aplicaciones de transporte. Diseñado para uso tanto en campo como en carretera, POWERTRAILER SR 331 se distingue por sus buenas propiedades de flotación en el campo, así como por su excelente tracción sobre asfalto u otras superficies duras y mejoradas. La construcción All Steel ofrece una gran capacidad de carga, extraordinaria estabilidad de la carcasa y una mayor duración del neumático. La nervadura especial del flanco proporciona una protección excepcional contra los impactos y los efectos del rozamiento del neumático, mientras que el talón hexagonal con tira de refuerzo asegura que el neumático encaje perfectamente en la llanta. Además, el dibujo multibloque de la banda de rodadura garantiza una resistencia a la rodadura reducida, una presión de contacto uniforme y una conducción suave. Gracias a todas estas características, POWERTRAILER SR 331 es sinónimo de ahorro de combustible y confort en carretera.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Camión cisterna • Remolque

|           |               |
|-----------|---------------|
| Version   | IMPLEMENT     |
| Type      | TL            |
| Tyre Size | 560/60 R 22.5 |
| LI/SS     | 165 D         |

## Dimensions International Standard

|                            |                  |
|----------------------------|------------------|
| Overall Width (mm)         | 555              |
| Overall Diameter (mm)      | 1245             |
| Static Loaded Radius (mm)  | 565              |
| Rolling Circumference (mm) | 3775             |
| SRI (mm)                   | 600              |
| Rim Rec                    | AG 16.00         |
| Rim Alt                    | 17.00 ; AG18.00  |
| ECE                        | E11-106R-0010087 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 5.00 |
| 65         | 5150 |

Printed on 28/04/2024 5:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..