

POWERTRAILER SR 331 - Especificaciones técnicas



Description

POWERTRAILER SR 331 es el nuevo neumático radial All Steel de BKT diseñado específicamente para remolques y camiones cisterna en aplicaciones de transporte. Diseñado para uso tanto en campo como en carretera, POWERTRAILER SR 331 se distingue por sus buenas propiedades de flotación en el campo, así como por su excelente tracción sobre asfalto u otras superficies duras y mejoradas. La construcción All Steel ofrece una gran capacidad de carga, extraordinaria estabilidad de la carcasa y una mayor duración del neumático. La nervadura especial del flanco proporciona una protección excepcional contra los impactos y los efectos del rozamiento del neumático, mientras que el talón hexagonal con tira de refuerzo asegura que el neumático encaje perfectamente en la llanta. Además, el dibujo multibloque de la banda de rodadura garantiza una resistencia a la rodadura reducida, una presión de contacto uniforme y una conducción suave. Gracias a todas estas características, POWERTRAILER SR 331 es sinónimo de ahorro de combustible y confort en carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	IMPLEMENT
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	169 D

Dimensions US Standard

Usa code	94075997
Overall Width (inch)	21.9
Overall Diameter (inch)	49
Static Loaded Radius (inch)	22.2
Rolling Circumference (inch)	148.6
Rim Rec	AG 16.00
Rim Alt	17.00 ; AG18.00
ECE	E11-106R-0010147

Load capacity (lbs)

mph/psi	46	52	58	65	73	80	87
5	14960	16340	17960	19100	20250	21640	23020
15	13130	14340	15760	16770	17780	18990	20210
25	11300	12350	13570	14430	15300	16350	17390
30	10050	10990	12070	12840	13610	14540	15480
40	8310	9080	9970	10610	11250	12020	12800
43	7560	8260	9070	9660	10240	10930	11640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 21:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..