

PRO RIB F2M - Especificaciones técnicas



Description

PRO RIB F2M es un neumático agrícola que se utiliza principalmente con los tractores 2WD/2RM en los trabajos del campo. Este neumático es particularmente idóneo para todas las operaciones que requieran un alto nivel de manipulación.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor 2WD

Industrial: Remolque

| | |
|-----------|---------------|
| Version | INDUSTRIAL |
| Type | TT |
| Tyre Size | 10.00 - 16 SL |
| LI/SS | 110 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94055081 |
| Ply Rating | 8 |
| Section Width (inch) | 10.8 |
| Overall Diameter (inch) | 35.2 |
| Static Loaded Radius (inch) | 16.1 |
| Rolling Circumference (inch) | 103.1 |
| Rim Rec | 8 LB |
| Rim Alt | W 8 L |
| ECE | E11-106R-005290 |
| TRA Code | F2M |

Load capacity (lbs)

| mph / psi | 44 |
|-----------|------|
| 25 | 2340 |

Printed on 27/04/2024 9:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..