

PRO RIB F2M - Especificaciones técnicas



Description

PRO RIB F2M es un neumático agrícola que se utiliza principalmente con los tractores 2WD/2RM en los trabajos del campo. Este neumático es particularmente idóneo para todas las operaciones que requieran un alto nivel de manipulación.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Tractor 2WD

Industrial: Remolque

Version	STANDARD
Type	TL
Tyre Size	16.5L - 16.1 SL
LI/SS	129 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	430
Overall Diameter (mm)	1072
Rim Rec	W 14 C
Rim Alt	W 14 CH
ECE	E11-106R-007860
TRA Code	F2M

Load capacity (Kg)

km/h / bar	2.80
40	1850

Printed on 27/04/2024 7:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..