

## PUDDLE SPECIAL (B) - Especificaciones técnicas



### Description

PUDDLE SPECIAL es un neumático agrícola R-2 particularmente desarrollado para utilizarlo en los arrozales. El diseño extra profundo de la banda de rodadura, además de la disposición especial de los tacos, asegura una óptima adherencia y una excelente tracción incluso en terrenos húmedos y blandos. El amplio elemento central ofrece una mejor capacidad de adaptación para las aplicaciones por carretera, así como excelentes prestaciones operativas. Además, PUDDLE SPECIAL muestra óptimas propiedades de auto-limpieza y una elevada duración.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Pulverizador

Version	STANDARD
Type	TL
Tyre Size	120/90 - 26
LI/SS	90 A2

## Dimensions International Standard

<b>Ply Rating</b>	6
<b>Section Width (mm)</b>	127
<b>Overall Diameter (mm)</b>	940
<b>Static Loaded Radius (mm)</b>	448
<b>Rolling Circumference (mm)</b>	2847
<b>Rim Rec</b>	4 JA
<b>ECE</b>	E11-106R-005236

## Load capacity (Kg)

km/h / bar	3.00
10	600

Printed on 09/05/2024 5:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..