

RIB 774 (A) - Especificaciones técnicas



Description

RIB 774 (A) es un neumático de sección baja para maquinaria agrícola que ofrece una elevada capacidad de carga, así como un amplio ciclo de vida del producto. Este neumático es ideal para aplicaciones de recogida de heno y de transporte con empacadoras de heno y remolques.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora • Remolque

Version	STANDARD
Type	TL
Tyre Size	12.0 - 18 (340/70 - 18)
LI/SS FREE ROLLING	150 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	342
Overall Diameter (mm)	902
Static Loaded Radius (mm)	414
Rolling Circumference (mm)	2688
Rim Rec	11.0
ECE	E11-106R-005355

Load capacity (Kg)

	km/h / bar	5.20
	10 FR	4690
	25 FR	3985
	30 FR	3750
	40 FR	3350

Printed on 26/04/2024 22:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..