

RIB 774 (A) - Especificaciones técnicas



Description

RIB 774 (A) es un neumático de sección baja para maquinaria agrícola que ofrece una elevada capacidad de carga, así como un amplio ciclo de vida del producto. Este neumático es ideal para aplicaciones de recogida de heno y de transporte con empacadoras de heno y remolques.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora • Remolque

Version	HD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	106 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	288
Rolling Circumference (mm)	1888
Rim Rec	AG 6.75
ECE	E11-106R-005259

Load capacity (Kg)

km/h / bar	5.00
10 FR	1330
25 FR	1130
30 FR	1065
40 FR	950

Printed on 27/04/2024 0:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..