

RIB 774 (A) - Especificaciones técnicas



Description

RIB 774 (A) es un neumático de sección baja para maquinaria agrícola que ofrece una elevada capacidad de carga, así como un amplio ciclo de vida del producto. Este neumático es ideal para aplicaciones de recogida de heno y de transporte con empacadoras de heno y remolques.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora • Remolque

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 250/65 - 14.5 |
| LI/SS FREE ROLLING | 119 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94027248 |
| Ply Rating | 12 |
| Section Width (inch) | 10 |
| Overall Diameter (inch) | 27.2 |
| Static Loaded Radius (inch) | 11.9 |
| Rolling Circumference (inch) | 77.9 |
| Rim Rec | AG 8.00 |
| Rim Alt | 6.75 |
| ECE | E11-106R-003532 |

Load capacity (lbs)

| mph / psi | 68 |
|-----------|------|
| 5 FR | 4200 |
| 15 FR | 3570 |
| 20 FR | 3360 |
| 25 FR | 3000 |

Printed on 15/04/2024 11:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..