

RIB 774 (B) - Especificaciones técnicas



Description

RIB 774 (B) es un neumático de sección baja para maquinaria agrícola, ideal para la agricultura moderna. Este neumático es idóneo para aplicaciones por carretera y fuera de carretera con maquinaria agrícola y remolques. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto. Hay disponible una versión "HD" para las operaciones más pesadas.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque
Industrial: Remolque

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	134 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	391
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2490
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004309

Load capacity (Kg)

km/h / bar	2.60
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120

Printed on 23/04/2024 11:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..