

## RIB 774 (C) - Especificaciones técnicas



### Description

RIB 774 (C) es un neumático de sección baja con base estrecha (narrow) para maquinaria agrícola. Este neumático es ideal para aplicaciones de recogida de heno y de transporte con empacadoras de heno y remolques por carretera y fuera de carretera. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Empacadora de heno • Cosechadora • Remolque

Version	STANDARD
Type	TL
Tyre Size	225/75 - 17.5
LI/SS FREE ROLLING	139 A8

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	220
<b>Overall Diameter (mm)</b>	775
<b>Static Loaded Radius (mm)</b>	360
<b>Rolling Circumference (mm)</b>	2310
<b>Rim Rec</b>	6.75
<b>ECE</b>	E11-106R-004591

## Load capacity (Kg)

	km/h / bar	9.00
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650

Printed on 27/04/2024 8:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..