

## RIB 774 (C) - Ficha técnica



### Description

RIB 774 (C) es un neumático de sección baja con base estrecha (narrow) para maquinaria agrícola. Este neumático es ideal para aplicaciones de recogida de heno y de transporte con empacadoras de heno y remolques por carretera y fuera de carretera. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Empacadora de heno • Cosechadora •  
Remolque

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
19.0/45 - 17	STANDARD	138 A8	10	16.00		455	845	387	2518	TL	E11-106R-004589
215/75 - 17.5	STANDARD	139 A8	16	6.75		220	775	360	2310	TL	E4-54R-0015341
215/75 - 17.5	STANDARD	134 A8	12	6.75		220	775	360	2310	TL	E11-106R-004590
225/75 - 17.5	STANDARD	134 A8	12	6.75		220	775	360	2310	TL	E11-106R-004657
225/75 - 17.5	STANDARD	139 A8	16	6.75		220	775	360	2310	TL	E11-106R-004591

Printed on 17/04/2024 7:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..