

RIB 775 - Ficha técnica



Description

RIB 775 es un neumático de telas cruzadas y sección baja, idóneo para el transporte y los trabajos del campo en los que se utilizan remolques y maquinaria agrícola. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
300/65 - 12	STANDARD	94011049	116 A8	8	9.0		12	27	12	79	TL	E11-106R-003582

Printed on 23/04/2024 1:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..