

RIB IMPLEMENT (B) - Especificaciones técnicas



Description

RIB IMPLEMENT (B) ha sido específicamente proyectado para maquinaria agrícola. Este neumático, ideal para las empresas agrícolas modernas, ha sido realizado con una mezcla resistente a los rastrojos, que garantiza una excelente protección contra los pinchazos. RIB IMPLEMENT (B) es un neumático que tiene una nervadura de la banda de rodadura que presenta 5 costillas y que se caracteriza por una carcasa particularmente durable que asegura un ciclo de vida prolongado. Es la mejor elección para todos los casos en los que se requiera una alta capacidad de carga y una baja resistencia al rodamiento.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TT
Tyre Size	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

Dimensions International Standard

Ply Rating	20
Section Width (mm)	425
Overall Diameter (mm)	1200
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

Load capacity (Kg)

	km/h / bar	4.0
	40 FR	4250
	50 FR	3750
	40 DW	3000
	50 DW	2725

Printed on 25/04/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..