

## RIB IMPLEMENT (B) - Especificaciones técnicas



### Description

RIB IMPLEMENT (B) ha sido específicamente proyectado para maquinaria agrícola. Este neumático, ideal para las empresas agrícolas modernas, ha sido realizado con una mezcla resistente a los rastrojos, que garantiza una excelente protección contra los pinchazos. RIB IMPLEMENT (B) es un neumático que tiene una nervadura de la banda de rodadura que presenta 5 costillas y que se caracteriza por una carcasa particularmente durable que asegura un ciclo de vida prolongado. Es la mejor elección para todos los casos en los que se requiera una alta capacidad de carga y una baja resistencia al rodamiento.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TT
Tyre Size	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

## Dimensions US Standard

Usa code	94046591
Ply Rating	20
Section Width (inch)	16.7
Overall Diameter (inch)	47.2
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

## Load capacity (lbs)

mph / psi	58
25 FR	9370
30 FR	8270
25 DW	6610
30 DW	6000

Printed on 25/04/2024 19:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..