

RIDEMAX FL 615 - Especificaciones técnicas



Description

RIDEMAX FL 615 es un neumático de flotación radial ideal para ejes no motrices de remolques, camiones cisterna y esparcidores. La estructura con cinturones de acero ofrece una alta resistencia a las perforaciones con mayor durabilidad y alta capacidad de carga. RIDEMAX FL 615 proporciona una baja resistencia al rodamiento en carretera con excelentes propiedades de autolimpieza en el campo. Su hombro redondeado y la amplia área de huella garantizan una óptima protección del suelo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STEEL BELTED
Type	TL
Tyre Size	800/65 R 32
LI/SS	185 D
LI/SS DRIVE WHEEL	185 D
LI/SS FREE ROLLING	185 D

Dimensions International Standard

Section Width (mm)	830
Overall Diameter (mm)	1853
Static Loaded Radius (mm)	834
Rolling Circumference (mm)	5624
SRI (mm)	875
Rim Rec	DW 27 B
ECE	E11-106R-007528

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6
65	3980	4350	5275	5830	6755	7680	8420	9250
50	4815	5265	6385	7055	8175	9295	10190	11195
40	5410	5915	7175	7930	9185	10445	11450	12580
30	6010	6570	7965	8805	10200	11600	12715	13970
25	6285	6870	8335	9210	10670	12135	13300	14615
10	7160	7830	9495	10490	12155	13820	15155	16650

Printed on 26/04/2024 10:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..