

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	650/50 R 22.5
LI/SS	163 D/160 E

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1222
Static Loaded Radius (mm)	535
Rolling Circumference (mm)	3715
SRI (mm)	575
Rim Rec	AG 20.00
ECE	E4-106R-001417

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1645	1845	2295	2610	3015	3420	3735	4095	4500
65	1780	2000	2490	2830	3270	3705	4050	4440	4875
50	2155	2420	3010	3425	3955	4485	4900	5370	5900
40	2425	2720	3385	3850	4445	5040	5505	6035	6630
25	2815	3160	3930	4470	5165	5860	6400	7015	7705
10	3205	3600	4480	5090	5880	6670	7285	7990	8775

Printed on 07/12/2023 21:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..