

RIDEMAX IT 697 (M+S) - Especificaciones técnicas



Description

RIDEMAX IT 697 M+S es la respuesta perfecta a las exigencias de los subcontratistas modernos en el sector de la agricultura para las operaciones realizadas durante el periodo invernal – perfecto para aplicaciones de transporte y municipales. Este neumático invernal para tractores, garantiza un agarre perfecto en todas las operaciones que se realizan en terrenos con hielo y nieve, sin ninguna necesidad de cadenas de nieve. Gracias a las ranuras de la banda de rodadura y a su carcasa robusta, el tractor se conduce con gran estabilidad, incluso a altas velocidades. El dibujo de la banda de rodadura ha sido proyectado para los trabajos más pesados y asegura una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/65 R 30 IND
LI/SS	156 D/161 A8

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1464
Static Loaded Radius (mm)	672
Rolling Circumference (mm)	4445
SRI (mm)	700
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E11-106R-003015

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1880	2320	2720	3160	3560	4000
50	2030	2505	2940	3415	3845	4320
40	2175	2685	3145	3655	4115	4625
30	2255	2785	3265	3790	4270	4800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 4:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..