

RM 500 - Ficha técnica



Description

RM 500 es un neumático radial con cinturones de acero, idóneo para las aplicaciones de cosecha con maquinarias agrícolas. El neumático está equipado con una robusta carcasa y un particular dibujo de la banda de rodadura que ofrecen una elevada capacidad de carga y una excelente resistencia a los cortes y los desgarros. Gracias a su amplia área de contacto, RM 500 asegura una óptima distribución de la presión en el terreno y una reducida compactación del suelo, así como una excelente tracción

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/70 R 24	STEEL BELTED	94062430	167 A8 / 155 A8	155 A8	167 A8	W 16 L	W 15 L	19.8	51.6	22.5	153.8	TL	E11-106R-005989
500/85 R 24	STEEL BELTED	94061570	182 A8 / 170 A8	170 A8	182 A8	W 16 L	W 15 L	20.5	57.5	24.5	172.5	TL	E11-106R-005991
500/80 R 28	STEEL BELTED	94063697	176 A8 / 164 A8	164 A8	176 A8	W 16 L	W 15 L	19.8	58.9	25	171.5	TL	E11-106R-005990
600/65 R 28	STEEL BELTED	94070961	177A8/165A8	165 A8	177 A8	W 18 L	W 20 L	23.2	58.5	25.2	170.9	TL	E11-106R-007699
600/65 R 28	STEEL BELTED	94063666	168 A8 / 156 A8	156 A8	168 A8	W 18 L	W 20 L	23.2	58.5	25.2	170.9	TL	E11-106R-005993
500/85 R 30	STEEL BELTED	94065097	176A8/164A8	164 A8	176 A8	W 16 L	W 15 L	21.1	63.4	26.5	186.8	TL	E11-106R-006398

Printed on 19/04/2024 18:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..