

## ROCK GRIP E4 - Especificaciones técnicas



### Description

ROCK GRIP (E-4) es un neumático de telas cruzadas especialmente proyectado para los camiones que se utilizan en las minas y las canteras. ROCK GRIP es el neumático ideal cada vez que las condiciones operativas para realizar transportes cortos en el sitio de trabajo requieran tanto resistencia al calor como protección a los cortes.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Dúmper rígido

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

## Dimensions US Standard

Usa code	94015504
Ply Rating	36
Overall Width (inch)	20.1
Overall Diameter (inch)	65
Static Loaded Radius (inch)	29.6
Rolling Circumference (inch)	192.3
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E4

## Load capacity (lbs)

mph / psi	91	123
30	20400	-
5	-	35300

Printed on 07/12/2023 13:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..