

ROCK GRIP E4 - Especificaciones técnicas



Description

ROCK GRIP (E-4) es un neumático de telas cruzadas especialmente proyectado para los camiones que se utilizan en las minas y las canteras. ROCK GRIP es el neumático ideal cada vez que las condiciones operativas para realizar transportes cortos en el sitio de trabajo requieran tanto resistencia al calor como protección a los cortes.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dúmper rígido

Version	STANDARD
Type	TL
Tyre Size	27.00 - 49

Dimensions International Standard

Ply Rating	54
Overall Width (mm)	740
Overall Diameter (mm)	2695
Static Loaded Radius (mm)	1253
Rolling Circumference (mm)	7985
Rim Rec	19.50/4.0
TRA Code	E4

Load capacity (Kg)

km/h / bar	6.50	8.75
50	27250	-
10	-	46970

Printed on 28/11/2023 21:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..