

ROCK GRIP E4 - Especificaciones técnicas



Description

ROCK GRIP (E-4) es un neumático de telas cruzadas especialmente proyectado para los camiones que se utilizan en las minas y las canteras. ROCK GRIP es el neumático ideal cada vez que las condiciones operativas para realizar transportes cortos en el sitio de trabajo requieran tanto resistencia al calor como protección a los cortes.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dúmper rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 - 49

Dimensions US Standard

Usa code	94044597
Ply Rating	48
Overall Width (inch)	29.1
Overall Diameter (inch)	106.1
Static Loaded Radius (inch)	49.3
Rolling Circumference (inch)	314.4
Rim Rec	19.50/4.0
TRA Code	E4

Load capacity (lbs)

mph / psi	83	112
30	55100	-
5	-	96500

Printed on 23/04/2024 18:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..