

## ROCK GRIP IND4 (RS) - Especificaciones técnicas



### Description

ROCK GRIP PORT INDUSTRIAL IND-4 (RS) es un neumático de bandas diagonales diseñado para apiladoras telescópicas en varias aplicaciones, incluidas las operaciones industriales y siderúrgicas. El compuesto especial ROCK GRIP garantiza una resistencia térmica especial, junto con una gran estabilidad y durabilidad.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Grúa Reach Stacker

|           |                 |
|-----------|-----------------|
| Version   | PORT INDUSTRIAL |
| Type      | TL              |
| Tyre Size | 18.00 - 25      |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Ply Rating                 | 40        |
| Overall Width (mm)         | 510       |
| Overall Diameter (mm)      | 1650      |
| Static Loaded Radius (mm)  | 753       |
| Rolling Circumference (mm) | 4885      |
| Rim Rec                    | 13.00/2.5 |
| Rim Alt                    | 15.00/2.5 |
| TRA Code                   | IND4      |

## Load capacity (Kg)

|            |       |
|------------|-------|
| km/h / bar | 10.00 |
| 10         | 22950 |

Printed on 19/04/2024 18:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..