

## ROCK GRIP IND4 (ECH) - Especificaciones técnicas



### Description

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) es un neumático de bandas diagonales diseñado para manipular contenedores vacíos en varias aplicaciones, incluidas las operaciones industriales y siderúrgicas. El compuesto especial ROCK GRIP garantiza una resistencia térmica especial, junto con una gran estabilidad y durabilidad.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Manipulador de contenedores vacios

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

## Dimensions US Standard

Usa code	94047413
Ply Rating	24
Overall Width (inch)	12.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	147.8
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND4

## Load capacity (lbs)

mph / psi	145
5	22640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 7:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..