

## ROCK GRIP L4 - Ficha técnica



### Description

ROCK GRIP (L-4) es un neumático de telas cruzadas para las palas cargadoras de ruedas que se utilizan en las operaciones de carga en terrenos difíciles. La especial mezcla de la banda de rodadura es particularmente resistente a cualquier tipo de corte, reduciendo el riesgo de perforación y consecuentemente el tiempo de parada del vehículo. La profundidad (L-4) de la banda de rodadura garantiza un ciclo de vida prolongado del neumático.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Buldócer • Pala cargadora

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	32	10.00/1.5		375	1410	649	4173	TL

Printed on 25/04/2024 7:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..