

ROCK GRIP (T) - Especificaciones técnicas



Description

ROCK GRIP (E-4) es ideal para utilizarlos en camiones volquetes en canteras y para realizar transportes cortos en las minas, llevando cargas pesadas. La especial mezcla de la banda de rodadura reduce al mínimo los cortes y las perforaciones incluso en los terrenos más difíciles. ROCK GRIP (E-4) ofrece una excelente tracción, así como un largo ciclo de vida.

UM

International Standard

Construction

❖ BIAS

Machinery

OTR: Volquete • Dúmper rígido

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	315
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	3755
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.60
80 LS/LD	3750

Printed on 18/04/2024 4:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..