

## ROCK STAR (SB SPL) - Especificaciones técnicas



### Description

ROCK STAR ha sido particularmente proyectado para medios de transporte en la carretera así como carriles de acero. ROCK STAR es un neumático de 32 telas con una capacidad de carga elevada. La mezcla especial de la banda de rodadura es particularmente resistente a los cortes y los desgarres, mientras que los cinturones de acero son sinónimo de durabilidad.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Vehículo de carretera-ferrocarril

Version	STEEL BELTED SPL
Type	TL
Tyre Size	14.00 - 24

## Dimensions International Standard

Ply Rating	32
Overall Width (mm)	390
Overall Diameter (mm)	1425
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

## Load capacity (Kg)

km/h / bar	10.00
10	14175

Printed on 23/04/2024 15:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..