

SIERRA MAX PRO - Especificaciones técnicas



Description

SIERRA MAX PRO es el neumático BKT perfecto para vehículos todoterreno en aplicaciones quad y ATV, incluso en competición. Su construcción radial y su huella especial ampliada proporcionan una marcha más suave y una tracción lateral y delantera optimizada. Se han diseñado tacos resistentes especiales para lograr una excelente tracción y un firme agarre en el terreno. Estas características aseguran una conducción muy cómoda, con seguridad y control. SIERRA MAX PRO ofrece un excelente rendimiento en todo tipo de terreno, desde los más duros hasta suelos sueltos.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Vehículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 25 X 8 R 12
LI/SS	43 N

Dimensions US Standard

Usa code	94067077
Section Width (inch)	7.9
Overall Diameter (inch)	24.8
Static Loaded Radius (inch)	11.3
Rolling Circumference (inch)	73.2
Rim Rec	6.5
Star Rating	***
ECE	E11-75R-005088

Load capacity (lbs)

mph / psi	7
87	340

Printed on 19/04/2024 18:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..