

## SIERRA MAX - Especificaciones técnicas



### Description

SIERRA MAX es el neumático BKT idóneo para las aplicaciones todo terreno y jardinería. Gracias a su construcción radial, este neumático ofrece una conducción notablemente más flexible y confortable, incluso en terrenos extremos como el desierto o en las superficies terrosas y rocosas. El particular dibujo de la banda de rodadura y una huella más ancha proporcionan una tracción anterior y lateral sin iguales.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Vehículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 25 X 8 R 12
LI/SS	43 N

## Dimensions US Standard

Usa code	94064786
Section Width (inch)	8.1
Overall Diameter (inch)	25.2
Static Loaded Radius (inch)	11.5
Rolling Circumference (inch)	74.8
Rim Rec	6.5
Star Rating	***
ECE	E11-75R-005088

## Load capacity (lbs)

mph / psi	7
87	340

Printed on 20/04/2024 9:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..