

SKID POWER (CHEVRON) - Especificaciones técnicas



Description

SKID POWER (CHEVRON) ha sido desarrollado para las minicargadoras (*skid steer*) que se utilizan en el sector de la construcción. Presenta una excelente tracción, así como elevadas propiedades de auto limpieza. SKID POWER (CHEVRON) es específicamente idóneo para las superficies terrosas, asegurando una elevada resistencia a los cortes y los desgarres.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

Version	IMPLEMENT
Type	TL
Tyre Size	7.00 - 15
LI/SS	106 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	203
Overall Diameter (mm)	762
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2295
Rim Rec	5.50 F
Rim Alt	6 LB
ECE	E11-106R-003583

Load capacity (Kg)

km/h / bar	4.10
40	950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 17:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..