

## SKID POWER HD (B) - Especificaciones técnicas



### Description

SKID POWER HD (B) ha sido proyectado para las minicargadoras (*skid steer*) que se utilizan en el sector de la construcción. Este neumático se caracteriza para la banda de rodadura extra profunda y la protección de los flancos, asegurando una excelente resistencia a los cortes y los desgarres, así como una extraordinaria duración. SKID POWER HD (B) es el neumático ideal para las superficies terrosas y los trabajos más pesados.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Minicargadora compacta

Version	STANDARD
Type	TL
Tyre Size	18 X 8.5 - 10
LI/SS	96 A2

## Dimensions US Standard

Usa code	94017751
Ply Rating	8
Section Width (inch)	8.1
Overall Diameter (inch)	18.3
Static Loaded Radius (inch)	8.3
Rolling Circumference (inch)	54.8
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-006774

## Load capacity (lbs)

	mph / psi	44
	5	1590
	10	1260
	15	1160

Printed on 18/04/2024 6:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..