

SKID POWER PLUS - Ficha técnica



Description

SKID POWER PLUS ha sido desarrollado para las minicargadoras (skid steer) que se utilizan en el ámbito de la construcción. Sus tacos más anchos garantizan una excelente tracción, así como óptimas propiedades de auto-limpieza. Este neumático se caracteriza por una banda de rodadura extra profunda, así como por una mayor protección de los flancos, asegurando de esta forma una excelente resistencia a los cortes y los desgarros, además de una extraordinaria duración. SKID POWER PLUS es el neumático ideal para las superficies de tierra. Su ancha área de contacto asegura una óptima estabilidad durante su empleo.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

| SIZE | Version | USACode | PR | RIM REC | RIM ALT | SW | OD | Type |
|-----------|----------|----------|----|---------|---------|-----|------|------|
| 10 - 16.5 | SPECIAL | 94057412 | 10 | 8.25 | | 9.9 | 30.5 | TL |
| 10 - 16.5 | STANDARD | 94054824 | 10 | 8.25 | | 9.9 | 30.5 | TL |
| 10 - 16.5 | STANDARD | 94054664 | 8 | 8.25 | | 9.9 | 30.5 | TL |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 11:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..